

**Сургут** (3462)77-98-35  
**Тверь** (4822)63-31-35  
**Томск** (3822)98-41-53  
**Тула** (4872)74-02-29  
**Тюмень** (3452)66-21-18  
**Ульяновск** (8422)24-23-59  
**Уфа** (347)229-48-12  
**Хабаровск** (4212)92-98-04  
**Челябинск** (351)202-03-61  
**Череповец** (8202)49-02-64  
**Ярославль** (4825)69-52-93

**Казахстан** (772)734-952-31

| ES size                    |                  |      | 16                                                                                      |        |        | 20                               |        |        | 25                                |       |        |
|----------------------------|------------------|------|-----------------------------------------------------------------------------------------|--------|--------|----------------------------------|--------|--------|-----------------------------------|-------|--------|
| Tooling system             |                  |      | Capto C4/C5, HSK50<br>(ISO/BT30)                                                        |        |        | Capto C5/C6, HSK63<br>(ISO/BT40) |        |        | Capto C6/C8, HSK100<br>(ISO/BT50) |       |        |
| Drive                      |                  |      | HT                                                                                      | B      | HS     | HT                               | B      | HS     | HT                                | B     | HS     |
| Torque                     | S1               | Nm   | 65                                                                                      | 42     | 22     | 100                              | 75     | 55     | 242                               | 200   | 140    |
|                            | S6-40%           |      | 81                                                                                      | 53     | 31     | 130                              | 100    | 72     | 300                               | 255   | 180    |
| Max speed                  |                  | rpm  | 9.000                                                                                   | 15.000 | 20.000 | 7.000                            | 12.000 | 15.000 | 3.500                             | 6.500 | 12.000 |
| Power                      | S1               | KW   | 29                                                                                      | 26     | 20     | 17                               | 25     | 24     | 38                                | 29    | 37     |
| Index system               | • Index clamping | Deg. | Every 45° (optional every 15°)                                                          |        |        |                                  |        |        |                                   |       |        |
|                            | • Index accuracy |      | Positioning ± 4" / repeatability ± 1,5"                                                 |        |        |                                  |        |        |                                   |       |        |
| Hydraulic working pressure |                  | Bar  | 50 +20%                                                                                 |        |        |                                  |        |        |                                   |       |        |
| Auxiliary services         |                  |      | Air seal, tool change air blust, ext. (25 bar) and int. (80 bar) coolant, motor cooling |        |        |                                  |        |        |                                   |       |        |