

Архангельск (8182)63-90-72
Астана (7172)727-132
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89
Иваново (4932)77-34-06

Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Липецк (4742)52-20-81

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16

Пермь (342)205-81-47
Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13

Сургут (3462)77-98-35
Тверь (4822)63-31-35
Томск (3822)98-41-53
Тула (4872)74-02-29
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Ярославль (4852)69-52-93

Киргизия (996)312-96-26-47

Россия (495)268-04-70

Казахстан (772)734-952-31

<https://diplomatic.nt-rt.ru/> || dcw@nt-rt.ru

SM(A)



Description:

The SM(A) turrets are driven by a brushless servomotor, with a clamping system hydraulically or pneumatically operated. Thanks to fast and soft indexing and high performances, they are specially conceived for high-production machines.

- Driven by servomotor
- Pneumatically or hydraulically operated
- Fast (SM) and superfast (SMA) indexing times
- High stiffness and loading capacity
- Supplied with integrated servomotor and relevant control unit (DDC4)

Technical information I.T.

6427

SM(A) size		10	12	16	20	25	32	40
Tool stations		8 - 12		8 - (10) - 12 - 16 - 24				
Max transportable Inertia	Kgm ²	0,3	1,8	3,5	8	14	32	100
Max tangential torque	Nm	400	950	1.800	3.600	7.200	13.000	30.000
Max tilting torque	(to push)	Nm	360	1.500	2.500	5.200	10.000	37.000
	(to lift)	Nm	180	1.250	2.200	4.500	8.000	17.500
Repeatability accuracy	Deg.	± 1,6"						
Indexing accuracy	Deg.	± 4"						
Coolant pressure	Bar	STD 14 / Option 30 / special 80						
Locking system	HYDR.	50±5 Bar	●	●	●	●	●	●
	PNEUM.	5±1 Bar	●	●	●	●	●	●